



www.hawkyre.com



TRUCK&BUS TYRE

**PREMIUM TYRE
MANUFACTURER**
SINCE 1975

ABOUT US















Company Profile

Hawk Tyre International Ltd, a global tire supplier integrating tire research and development, production and marketing, now mainly deals with four segments including truck and bus tires, OTR tires, agricultural tires and industrial tires. Relying on over 40 years of tire manufacturing experience and market accumulation, Hawk Tyre products feature high loading capacity, super wear-resistance, and great adaptation to complex road conditions. Credited with ISO9001, CCC, DOT, ECE, SMARTWAY, GCC, SNI and other international certifications, the company's brands "HAWKWAY" "SUPERHAWK" "YINGBA" "MARVEMAX" are distributed to more than 80 countries in Southeast Asia, America, Australia and Africa etc, and all received with positive feedback by global partners.

Look forward to the future, Hawk Tyre will continue to improve the user experience towards the product and focus on providing all partners with full range customized services including professional pre-sales training, tracking guidance and advertisement support, after-sales assistance to solve problems. To achieve customer's satisfaction is our pursuit.

Product Categories

	ALL POSITION/STEER	DRIVE	TRAILER
 <p>HIGHWAY (Long Haul)</p>	 HK700  HK720  HK723  HK725  HK730  HK755  HK826  HK861  HK862  HK863  HK865  HK867  HK886  HK896  HK086	 HK785  HK839  HK860  HK869  HK870  HK878	 HK806  HK876T  HK897
 <p>REGIONAL (Mixed Road)</p>	 HK701  HK703  HK735  HK802  HK810  HK887	 HK732  HK733  HK750  HK782  HK828  HK852  HK858  HK859  HK898	
 <p>OFF THE ROAD</p>	 HK707  HK710  HK789  HK792  HK808  HK809  HK893  HK203  HK206		



HK700



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
6.50R16LT	12PR	10.5	5.50F	TT	110/105	L	750	185	670	670	1060	925
7.00R16LT	14PR	10.5	5.50F	TT	118/114	L	775	200	770	770	1320	1180
7.50R16LT	14PR	13.5	6.00G	TT/TL	122/118	L	805	215	770	770	1500	1320
8.25R20	16PR	15.0	6.50	TT	139/137	K	974	236	930	930	2430	2300

Performance Description:

- Applied for express way and urban road, all position of the light trucks and bus.
- Rib pattern, extra sideslip resistance, pitch pattern designed.
- Low noise. By four straight main slots and it delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.



HK701



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
6.50R16LT	12PR	10.5	5.50F	TT	110/105	L	750	185	670	670	1060	925
11.00R20	18PR	17.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	17.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650
13R22.5	20PR	19.0	9.75	TL	156/153	K	1136	320	930	930	4000	3650

Performance Description:

- Applied for highway, urban and country road, all position of trucks and bus.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.



HK703



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
7.00R16LT	14PR	13.0	5.50F	TT/TL	118/114	L	775	200	770	770	1320	1180
7.50R16LT	14PR	15.0	6.00G	TT/TL	122/118	L	805	215	770	770	1500	1320
8.25R16LT	16PR	16.0	6.50H	TT/TL	128/124	L	855	235	770	770	1800	1600
10.00R20	18PR	17.0	7.50	TT	149/146	K	1054	278	930	930	3250	3000

Performance Description:

- Applied for highway, urban and country road, all position of trucks and bus.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.



HK707



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
9.00R20	16PR	22.0	7.00F	TT	144/142	B	1019	259	900	900	2800	2650
10.00R20	18PR	23.5	7.50F	TT	149/146	B	1054	278	930	930	3250	3000
11.00R20	18PR	25.0	8.00	TT	152/149	B	1085	295	930	930	3550	3250
12.00R20	20PR	25.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650
12.00R24	24PR	25.0	8.50	TT	164/161	B	1226	315	900	900	5000	4625

Performance Description:

- Applied for short-haul, low speed, and heavy loaded dumping trucks.
- Excellent stab-resistance, anti-eccentric worn, avulsion resistance.
- Aggressive lug pattern design provides excellent grip and traction performance.



HK710



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	25.0	8.00	TT	152/149	B	1085	295	930	930	3550	3250
12.00R20	22PR	25.5	8.50	TT	158/155	B	1125	315	970	970	4250	3875

Performance Description:

- Applied for short-haul, low speed, and heavy loaded dumping trucks.
- Special tread compound with high wear-resistance, suitable for mining application and construction sites.
- Aggressive lug pattern design provides excellent grip and traction performance.



HK720



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	17.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

- Super wide and extremely wear-resistant.
- Special designed for long haul. Perform well on good road condition.
- Contact area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Strong bead structure insures longer endurance and lifespan.



HK723



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	19.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

- Application for passenger vehicle and truck on express way and city roads.
- The wide and flat tread provides excellent wear resistance. The deep pattern offers long life.
- Four belts construction and closed shoulder resistant uneven wear.
- Strong carcass and belts provide more load capacity.



HK725



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	18.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

- Super wide and extremely wear-resistant.
- Special designed for long haul. Perform well on good road condition high speed.
- Contact area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Strong bead structure insures longer endurance and lifespan.



HK730



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	18.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

- Super wide and extremely wear-resistant.
- Mixed highway and freeway for long distance and national transportation service.
- Contact area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Enhanced channel siping and wide grooves allow for premium wet and dry traction.



HK732



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
9.00R20	16PR	17.5	7.00	TT	144/142	K	1019	259	900	900	2800	2650
10.00R20	18PR	18.0	7.50	TT	149/146	K	1054	278	930	930	3250	3000
11.00R20	18PR	18.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	19.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650

Performance Description:

- Applicable for driving wheels of heavy truck.
- Unique pattern design offers good pulling force.
- Special tread compound offers excellent cut-resistance.
- Suitable for short distance on mining, bad roads and good roads.



HK733



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	17.0	8.00	TT	152/149	K	1094	293	930	930	3550	3250
12.00R20	20PR	17.0	8.50	TT	156/153	K	1136	315	900	900	4000	3650

Performance Description:

- Super Wide and Extremely wear-resistant.
- Applied for short-haul and heavy loaded dumping trucks.
- Special tread compound with high wear-resistant, suitable for mining application and construction sites.
- Aggressive block pattern design provides excellent grip and traction performance.



HK735



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12.00R20	20PR	21.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650

Performance Description:

- Aggressive block design provides outstanding traction on rough roads.
- Suitable for all season and all position application on mud and sand terrain with some short on high-way use.
- Cool-running compound enhances toughness casing.



HK750



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	19.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	20.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650

Performance Description:

- Applied for short-haul , low speed, and heavy loaded dumping trucks.
- Special tread compound with high cut-resistant, suitable for mining application and construction sites.
- Aggressive block pattern design provides excellent grip and traction performance.



HK755



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	17.5	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

- Super Wide and Extremely wear-resistant.
- Special designed for long haul. Perform well on good road condition high speed.
- Contact Area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Strong bead structure insures longer endurance and lifespan.



HK782



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	19.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

- Applied for express way, highway and urban road, drive position of truck.
- Special tread compound design for lower heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tyre load capacity.



HK785



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	20.0	9.00	TL	152/149	L	1095	300	930	930	3550	3250

Performance Description:

- Applied for national highway, standard highway with normal condition.
- Driving wheel of long haul trucks tractor trucks, Good traction, braking and sideslip resistance.
- Extra deep tread provides excellent grip and driving capacity and also enhance tyre safety and abrasion resistance performance.



HK789



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
10.00R20	18PR	23.5	7.50	TT	149/146	B	1061	275	930	930	3250	3000

Performance Description:

- Applied for short-haul , low speed and heavy loaded dumping trucks.
- Special tread compound with high wear-resistant, suitable for mining application and construction sites.
- Aggressive lug pattern design provides excellent grip and traction performance.



HK792



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12.00R20	20PR	25.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650

Performance Description:

- Applicable for driving wheels. For short distance with low speed on mining and bad roads.
- Pattern design offers excellent pulling force.
- Special tread compound offers excellent cut resistance.
- Reinforced bead design provides excellent load capacity.



HK802



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
7.00R16LT	14PR	10.5	5.50F	TT	118/114	L	775	200	770	770	1320	1180
7.50R16LT	14PR	13.5	6.00G	TT/TL	122/118	L	805	215	770	770	1500	1320
8.25R16LT	16PR	14.5	6.50H	TT	128/124	L	855	235	770	770	1800	1600
8.25R20	16PR	15.0	6.50	TT	139/137	K	974	236	930	930	2430	2300
9.00R20	16PR	15.5	7.00	TT	144/142	K	1019	259	900	900	2800	2650
10.00R20	18PR	16.0	7.50	TT	149/146	K	1054	278	930	930	3250	3000
11.00R20	18PR	15.5	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	16.0	8.50	TT	156/153	K	1125	315	930	930	4000	3650
12.00R24	20PR	16.0	8.50	TT	160/157	K	1226	315	930	930	4500	4125
205/85R16LT	14PR	10.5	6J	TL	117/115	L	775	200	575	575	1285	1215
11R22.5	16PR	17.5	8.25	TL	146/143	M	1054	279	830	830	3000	2725
11R24.5	16PR	17.5	8.25	TL	149/146	L	1104	279	830	830	3250	3000
295/80R22.5	18PR	17.5	9.00	TL	152/149	M	1044	298	900	900	3550	3250
12R22.5	18PR	17.0	9.00	TL	152/148	L	1085	300	930	930	3550	3150
315/80R22.5	20PR	17.5	9.00	TL	156/150	L	1076	312	850	850	4000	3350
	22PR								950	950	5450	5000

Performance Description:

- Applied for express way and urban road, all position of the trucks and bus.
- It delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.



HK806



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
385/65R22.5	20PR	15.0	11.75	TL	160	K	1072	389	930	---	4500	---
	22PR								950	---	4750	---

Performance Description:

- Application for all position on mixed highway and freeway.
- Special tread compound provides low heating-up, smooth wear & cut resistance, and low rolling resistance.
- Suitable for heavy duty truck and bus.



HK808



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
7.50R16LT	14PR	16.5	6.00G	TT	122/118	B	805	215	770	770	1500	1320
8.25R16LT	16PR	17.0	6.50H	TT	128/124	B	855	235	770	770	1800	1600
11.00R20	18PR	24.0	8.00	TT	152/149	B	1093	288	930	930	3550	3250
12.00R20	20PR	24.0	8.50	TT	156/153	B	1131	311	900	900	4000	3650
12.00R24	20PR	25.0	8.50	TT	160/157	B	1228	312	900	900	4500	4125

Performance Description:

- Applied for bad road conditions including mining application of heavy duty workloads, short haul, low speed.
- Large lug pattern design provides excellent grip performance, wear-resistant compound design provides super tread life.
- Excellent stab-resistance, anti-eccentric worn, avulsion resistance and tread wear ability.



HK809



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
7.50R16LT	14PR	17.0	6.00F	TT	122/118	B	815	215	770	770	1500	1320
8.25R16LT	16PR	17.0	6.50H	TT	128/124	B	865	235	930	930	1800	1600
8.25R20	16PR	17.0	6.50	TT	139/137	B	947	236	930	930	2430	2300

Performance Description:

- Applied for bad road conditions including mining application of heavy duty workloads, short haul, low speed.
- Large lug pattern design provides excellent grip performance, wear-resistant compound design provides super tread life.
- Excellent stab-resistance, anti-eccentric worn, avulsion resistance.



HK810



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	24.5	8.25	TL	146/143 148/145	G	1054	279	830	830	3000	2725
12R22.5	18PR	24.0	9.00	TL	152/149	L	1085	300	900	900	3550	3250
295/80R22.5	18PR	21.0	9.00	TL	152/149	F	1044	298	900	900	3550	3250
315/80R22.5	22PR	25.0	9.00	TL	167/164	D	1100	312	950	950	5450	5000

Performance Description:

- Applied for short-haul, low speed and heavy loaded dumping trucks.
- Special tread compound with high wear-resistance, suitable for mining application and construction sites.
- Aggressive lug pattern design provides excellent grip and traction performance.



HK826



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
275/70R22.5	18PR	20.0	8.25	TL	148/145	M	964	270	900	900	3150	2900
11R22.5	16PR	19.5	8.25	TL	146/143	M	1054	279	830	830	3000	2725

Performance Description:

- Design for good tread wear and sidewall scuff resistance.
- Special tread compound design for lower heat build-up, excellent puncture and cut resistance.
- Suitable for urban bus.



HK828



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
7.00R16LT	14PR	10.5	5.50F	TT	118/114	L	783	200	770	770	1320	1180
7.50R16LT	14PR	14.5	6.00F	TT	122/118	L	815	215	770	770	1500	1320
8.25R16LT	16PR	15.5	6.50H	TT	128/124	L	865	235	770	770	1800	1600
11.00R20	18PR	19.0	8.00	TT	152/149	K	1096	293	930	930	3550	3250
12.00R20	20PR	19.5	8.50	TT	156/153	K	1136	315	930	930	4000	3650
11R22.5	16PR	19.0	8.25	TL	146/143	M	1054	279	830	830	3000	2725

Performance Description:

- Special tread compound and design enable low heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tyre load capacity.
- Four ribs with transverse deep grooves optimize speed and traction performance, provides excellent performance on wet road surface.
- Suitable for light truck, truck, heavy duty truck and bus on general roads and good roads.



HK839



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
295/80R22.5	18PR	19.0	9.00	TL	152/149	L	1044	298	900	900	3550	3250

Performance Description:

- Applied for national highway, standard highway with normal condition.
- Driving wheel of long haul trucks tractor trucks, good traction, braking and sideslip resistance.
- Extra deep tread provides excellent grip and driving capacity and also enhance tyre safety and abrasion resistance performance.



HK852



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	18.5	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	18.5	8.50	TT	156/153	K	1125	315	900	900	4000	3650

Performance Description:

- Applicable for drive axle on unpaved road.
- Robust tread block provides outstanding traction on mud road surface.
- Special groove design with stone ejector prevent from stone penetration.
- Durable tyre carcass and improved tread compound help to resist.



HK858



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
7.00R16LT	14PR	10.5	5.50F	TT	118/114	L	775	200	770	770	1320	1180
7.50R16LT	14PR	14.0	6.00G	TT	122/118	L	805	215	770	770	1500	1320
8.25R16LT	16PR	15.0	6.50H	TT	128/124	L	855	235	770	770	1800	1600
9.00R20	16PR	15.5	7.00F	TT	144/142	K	1019	259	900	900	2800	2650
10.00R20	18PR	16.0	7.50F	TT	149/146	K	1054	278	930	930	3250	3000

Performance Description:

- Applied for express way, highway and urban road, drive position of truck.
- Special tread compound design for lower heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tyre load capacity.



HK859



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	23.5	8.25	TL	146/143	M	1054	279	830	830	3000	2725
295/80R22.5	18PR	19.0	9.00	TL	152/149	L	1044	298	900	900	3550	3250
315/80R22.5	20PR	20.5	9.00	TL	156/150	L	1076	312	850	850	4000	3350
	22PR				167/164				950	950	5450	5000

Performance Description:

- Open shoulder drive tire applied for urban and country road, drive position of truck.
- Reinforced steel belt carcass enhances casing strength and maximizes load capacity.
- Special wear-resistant tread design of low heat build-up.



HK860



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	18.0/20.5	8.25	TL	146/143	M	1054	279	830	830	3000	2725
11R24.5	16PR	18.0	8.25	TL	149/146	L	1104	279	830	830	3250	3000
295/75R22.5	16PR	18.0	8.25	TL	146/143	L	1014	298	830	830	3000	2725

Performance Description:

- Mixed highway and freeway for long distance and national transportation service, drive position tubeless type for both city and highway applications.
- Special tread compound design for lower heat build-up, lower rolling resistance and minimized gasoline consumption.
- Special tread design offers good grasp capability on wet road and minimized driving noise.



HK861



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
215/75R17.5	18PR	13.5	6.00	TL	135/133	J	767	211	900	900	2180	2060
11R22.5	16PR	14.0	8.25	TL	146/143	M	1051	279	830	830	3000	2725

Performance Description:

- Suitable for low platform, specialty trailers and truck.
- Dual compound rubber helps ensure cool operating temperatures while upper tread abrasion resistance helps keep wear rates low.
- Unique tread pattern design minimizes side sliding on wet road.



HK862



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
295/80R22.5	18PR	15.0	9.00	TL	152/149	M	1044	298	900	900	3550	3250
315/80R22.5	20PR	15.0	9.00	TL	156/150	L	1076	312	850	850	4000	3350

Performance Description:

- Suitable for long journey, applied to steer wheels for highway and good road condition.
- Unique tread design and compound for lower heat and lower rolling resistance and minimized gasoline consumption.
- Horizontal rib design offers the top guiding and stability at high speed service, which also provides the excellent stone ejection performance and super grip on wet road.



HK863



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	15.0	8.25	TL	146/143	M	1054	279	830	830	3000	2725
12R22.5	18PR	15.0	9.00	TL	152/148	L	1095	300	850	850	3550	3150

Performance Description:

- Mixed highway and freeway for long distance and national transportation service, high speed.
- Special tread compound offers excellent performance of lower heat build-up and cut resistance, super grip on wet road and improved riding comfort.
- Suitable for local and inter-state bus and truck.



HK865



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	15.0	8.25	TL	146/143	M	1054	279	830	830	3000	2725
295/75R22.5	16PR	15.0	9.00	TL	146/143	L	1014	298	830	830	3000	2725
11R24.5	16PR	15.0	8.25	TL	149/146	L	1104	279	830	830	3250	3000
285/75R24.5	16PR	15.0	8.25	TL	147/144	L	1050	283	830	830	3075	2800
ST235/85R16	14PR	9.50	6½	TL	129/125	L	806	235	760	760	2000	1750

Performance Description:

- Smartway certified eco friendly all position or steer tire for long haul.
- Optimum tread design guarantees even wear in trailer axle positions.
- Rib stone rejectors preserve casing integrity.



HK867



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
215/75R17.5	16PR	15.0	6.00	TL	132/129	J	767	211	900	900	2000	1850
225/70R19.5	14PR	14.0	6.75	TL	128/126	M	811	226	760	760	1800	1700
235/75R17.5	16PR	15.0	6.75	TL	132/129	J	797	233	830	830	2000	1850
245/70R19.5	14PR 16PR	14.0	7.50	TL	133/131 135/133	M	811	226	760 830	760 830	2060 2180	1950 2060
265/70R19.5	18PR	15.0	7.50	TL	143/141	J	867	262	825	825	2725	2575
255/70R22.5	16PR	14.5	7.50	TL	140/137	M	930	255	830	830	2500	2300
275/70R22.5	16PR 18PR	15.0	8.25	TL	144/141 148/145	M	958	276	830 900	830 900	2800 3150	2575 2900
11R22.5	16PR	15.0	8.25	TL	146/143	M	1054	279	830	830	3000	2725

Performance Description:

- Applied for express way, highway and urban road, all position of the light truck and bus.
- Horizontal groove design between ribs prevents slippage and side-slippage.
- Strong bead structure insures longer endurance and lifespan.



HK869



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	21.0	8.25	TL	146/143	L	1065	279	830	830	3000	2725
295/75R22.5	16PR	22.0	8.25	TL	146/143	K	1020	298	830	830	3000	2725
11R24.5	16PR	24.0	8.25	TL	149/146	K	1116	279	850	850	3250	3000
285/75R24.5	16PR	22.0	8.25	TL	147/144	K	1056	283	830	830	3075	2800

Performance Description:

- Smartway certified eco friendly all position or steer tire for long haul.
- Optimum tread design guarantees even wear in drive axle positions.
- Rib stone rejectors preserve casing integrity.



HK870



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	21.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250
315/80R22.5	20PR	22.0	9.00	TL	156/153	L	1076	312	850	850	4000	3650

Performance Description:

- Applied for national highway, standard highway with normal condition.
- Driving wheel of long haul trucks tractor trucks, Good traction, braking and sideslip resistance.
- Extra deep tread provides excellent grip and driving capacity and also enhance tyre safety and abrasion resistance performance.



HK876T



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	14PR	9.50	8.25	TL	144/142	M	1054	279	720	720	2800	2650
295/75R22.5	14PR	9.50	8.25	TL	144/141	M	1014	298	760	760	2800	2575

Performance Description:

- Smartway certified eco friendly trailer tire for long haul.
- Optimum tread design guarantees even wear in trailer axle positions.
- Rib stone rejectors preserve casing integrity.



HK878



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	21.0	8.25	TL	146/143	M	1065	279	830	830	3000	2725
12R22.5	18PR	19.0	9.00	TL	152/148	L	1095	300	850	850	3550	3150

Performance Description:

- Applied for national highway, standard highway with normal condition.
- Driving wheel of long haul trucks tractor trucks, good traction, braking and sideslip resistance.
- Extra deep tread provides excellent grip and driving capacity and also enhance tyre safety and abrasion resistance performance.



HK886



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	18.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

- Three ribs ensure even wear and comfortable riding.
- Sipped zig-zag rib helps improve traction on wet and muddy surface.
- Deep circumferential grooves improve efficient water evacuation, lateral stability, and long tyre life.



HK887



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12.00R20	20PR	18.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650

Performance Description:

- Application for all position on the most types of roads.
- Special tread pattern design provides low heat build-up, special compound design provides excellent puncture and cut resistance.
- Four ribs design with transverse grooves optimize speed and traction performance, provides excellent performance on wet road surface.
- Suitable for truck and heavy-duty truck.



HK893



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12.00R20	20PR	24.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650

Performance Description:

- Applicable for driving wheels. For short distance with low speed on mining and bad roads.
- Pattern design offers excellent pulling force.
- Special tread compound offers excellent cut resistance.
- Reinforced bead design provides excellent load capacity.



HK896



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	16.0	9.00	TL	152/148	L	1085	300	930	930	3550	3150

Performance Description:

- Designed for highway transportation with good road conditions.
- Unique tread compound design with low rolling resistance, low heat build-up and minimized gasoline consumption.
- Enhanced channel siping and wide grooves allow for premium wet and dry traction.



HK897



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
295/60R22.5	18PR	15.5	9.00	TL	150/147	M	926	292	900	900	3350	3075

Performance Description:

- Computer designed tyre structure provides excellent footprint profile and ensures superior comfort.
- Special tread compound guarantees low rolling resistance help to reduce fuel consumption.



HK898



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
10.00R20	18PR	16.0	7.50	TT	149/146	K	1054	278	930	930	3250	3000

Performance Description:

- Suitable for heavy duty truck, applied for city, town and uneven roads, especially off the roads with stones, gravels in mining and construction sites.
- Aggressive tread pattern and extra depth tread ensures the long hauling on tough roads.



HK086



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12.00R24	20PR	15.5	8.50	TT	160/157	K	1226	315	900	900	4500	4125

Performance Description:

- High powered mixed; Quasi-sovereign tread; Integrative shoulder pattern.
- High loading capability; Suitable for all kinds of road conditions.
- Special tread compound design for lower heat build-up, perform well in hot weather.



HK203



Tyre Size	Star Pating	Tread Pattern	Standard Rim	Tube Type	Load/Speed Index	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									10km/h	50km/h	10km/h	50km/h
14.00R25	★★★	E4	10.00/1.5	TT	188B/169A2	38	1370	375	950	700	10000	5800
16.00R25	★★★	E4	11.25/2.0	TT	184B/167A2	43	1495	430	550	450	9000	5450
					195B/177A2				800	650	12150	7300

Performance Description:

- Aggressive tread pattern design provides excellent stability and grip capability.
- Unique tread compound supplies best abrasion resistance and chunking resistance properties.



HK206



Tyre Size	Star Pating	Tread Pattern	Standard Rim	Tube Type	Load/Speed Index	Tread Depth (mm)	Outer Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									10km/h	50km/h	10km/h	50km/h
13.00R25	★★★	E4	8.50	TT	163B/182A2	33	1301	351	825	700	8500	4875
14.00R25	★★★	E4	10.00	TT	168B/186A2	33	1368	375	800	650	9500	5600
					169B/188A2				950	700	10000	5800

Performance Description:

- Aggressive tread pattern design provides excellent stability and grip capability.
- Unique tread compound supplies best abrasion resistance and chunking resistance properties.

SPEED SYMBOL

The SPEED SYMBOL indicates the speed at which the tire can carry a load corresponding to its load index service conditions specified by HAWKWAY.

Speed Symbol	Speed(km/h)	Speed Symbol	Speed(km/h)
B	50	M	130
C	60	N	140
D	65	P	150
E	70	Q	160
F	80	R	170
G	90	S	180
J	100	T	190
K	110	U	200
L	120	H	210